

PRODUCT SPECIFICATION SHEET

Quasar Decorative LED Illuminator



Rev. C5



The UFO Quasar LED. Extremely high powered light output and full DMX , 0-10V, 1-10V and manual control make this an LED illuminator unparalleled in its light output and control capabilities.

Utilises industry standard protocols to control the unit's dimming effects. This is the ultimate light source for illuminating fiber optic effect lighting when a crisp, bright, controllable white light is required.

Features an LCD display which provides user feedback for ease of use.

Available in a range of color temperatures and in both >80CRI and >90 CRI versions.

Fitted with a standard 30mm fiber port connector, this illuminator is suitable for both new installations and retro-fitting to existing fiber optic installations.

GENERAL INFORMATION

Port connector size	30mm (1.18") diameter
Fiber type	Glass / PMMA
Material/Finish	Aluminum, grey powdercoat (RAL7024)
Dimensions (L x W x H)	309mm (12.1") x 266mm (10.5") x 186mm (7.3")
Weight	4.72kg (10.4lb)
Operating Environment	Indoor use - IP20
Min Ambient Temp.	-10°C (14°F)
Max Ambient Temp.	+45°C (113°F)

LIGHTING AND CONTROL INFORMATION

Control Functionality	0-10V \ 1-10V \ DMX \ Manual
DMX Functionality	User addressable to 512
DMX Channels	5 channels
Effects Wheel Options & Functionality	Color and Twinkle Controlled by 0-10V, DMX and Manual

LED ARRAY DATA

LED Array Type	White Light - 22mm LES CoB
LED Array Power	150W
LED Array Model	Bridgelux Gen 8 V22 Series
LED Array Life (L70, B10)	50,000 hours typical @ 25°C (77°F)

STANDARD CRI (>80) RANGE OPTIONS



Lumens direct from common end @ 90°C target temperature

3000K : 21499lm	4000K : 22131lm	5000K : 22396lm
5700K : 21499lm	6500K : 22637lm	

HIGH CRI (>90) RANGE OPTIONS

Lumens direct from common end @ 90°C target temperature

2700K : 16693lm	3000K : 17452lm	4000K : 18464lm
-----------------	-----------------	-----------------



Note that drawing dimensions are shown in mm

ELECTRICAL CHARACTERISTICS

Supply Voltage	90 - 305Vac
Mains Running Current	0.8A @ 240Vac
Mains Voltage VA rating	186VA
Fan Type	Sunon 92mm - 32dBA
Motor Type	Rotalink 25C13/YSOLPSL3E - 12V - 60:1

AVAILABLE ACCESSORIES

MAS0504026R5	Weatherproof Enclosure
UFO Unidim CVD1	Remote manual dimmer with plate
UFO Unidim CVD3	Remote current sink dimmer with plate
UFO Unifeed SFD1	Separate feed unit for decorative wheel

LIGHT SOURCE PRODUCT CODES

MODEL	COLOR TEMPERATURE		CRI		EFFECTS	
UFO QUA	3000K	30	80	80	None	X
	4000K	40			Color Wheel	C
	5000K	50			Twinkle Wheel	T
	5700K	57			Seperate Feed Color Wheel	CF
	6500K	65				
	2700K	27	90	90		
	3000K	30				
	4000K	40				

UFO QUA - - -

e.g, UFO QUA-30-90-CF



Universal Fibre Optics Ltd
Home Place \ Coldstream
TD12 4DT \ UK
+44 (0)1890 883416 \ www.ufo.lighting

Universal Fiber Optic Lighting USA LLC
1749 Northgate Blvd
Sarasota \ FL34234 \ USA
941-343-8115 \ www.fiberopticlighting.com

UFO Licht GmbH
Andreasstraße 20
93059 Regensburg \ Deutschland
+49 (0)9491 955880 \ www.ufo-licht.de