

PRODUCT SPECIFICATION SHEET

Quasar White Light LED Illuminator



Rev. C3



The UFO Quasar LED. Extremely high powered light output and full DMX , 0-10V, 1-10V and manual control make this an LED illuminator unparalleled in its light output and control capabilities.

Utilises industry standard protocols to control the unit's dimming effects. This is the ultimate illuminator for illuminating fiber optic effect lighting when a crisp, bright, controllable white light is required.

Features an LCD display which provides user feedback for ease of use.

Available in a range of color temperatures and in both >80CRI and >90 CRI versions.

Fitted with a standard 30mm fiber port connector, this illuminator is suitable for both new installations and retro-fitting to existing fiber optic installations.

GENERAL INFORMATION

Port connector size	30mm (1.18") diameter
Fiber type	Glass / PMMA
Material/Finish	Aluminum, grey powdercoat (RAL7024)
Dimensions (L x W x H)	309mm (12.1") x 236mm (9.3") x 158mm (6.2")
Weight	3.96kg (8.73lb)
Operating Environment	Indoor use - IP20
Min Ambient Temp.	-10°C (14°F)
Max Ambient Temp.	+45°C (113°F)

LIGHTING AND CONTROL INFORMATION

Control Functionality	0-10V \ 1-10V \ DMX \ Manual dimming
DMX Functionality	User addressable to 512
DMX Channels	2 channels

LED ARRAY DATA


LED Array Type	White Light - 22mm LES CoB
LED Array Power	150W
LED Array Model	CLU048-1818-C4
LED Array Life (L70, B10)	50,000 hours typical @ 25°C (77°F)

STANDARD CRI (>80) RANGE OPTIONS

3000K : 17974lm	4000K : 18438lm	5000K : 18653lm
5700K : 18840lm	6500K : 18992lm	

HIGH CRI (>90) RANGE OPTIONS

2700K : 14805lm	3000K : 15400lm	4000K : 15633lm
5700K : 16174lm		



Note that drawing dimensions are shown in mm

ELECTRICAL CHARACTERISTICS

Supply Voltage	90 - 305Vac
Mains Running Current	0.8A @ 240Vac
Mains Voltage VA rating	186VA
Fan Type	Sunon 92mm - 32dBA

AVAILABLE ACCESSORIES

MAS0504026R5	Weatherproof Enclosure
UFO Unidim CVD1	Remote manual dimmer with plate
UFO Unidim CVD3	Remote current sink dimmer with plate

ILLUMINATOR PRODUCT CODES

MODEL	COLOR TEMPERATURE		CRI		EFFECTS	
	K					
UFO QUA	3000K	30	80	80	None	X
	4000K	40			Emergency White light	E
	5000K	50				
	5700K	57				
	6500K	65				
	2700K	27	90	90		
	3000K	30				
	4000K	40				
	5700K	57				

UFO QUA - [] - [] - []

e.g. UFO QUA-30-90-X

